

# High performance HydroWax dispersions

Micro protection and the potential of synthetic waxes

### HydroWax's advantages

Wood-based panel products are continuously improved. The growing shortage of raw materials and increased final product requirements has resulted in changes in wood composition, density and gluing systems. Innovative wood-based panel products for new applications require accurately adjustable and more powerful hydrophobing additives. Hywax's ever increasing process performance standards, constant quality and reliable delivery of dispersions ensures optimal operation of the production facility. Safety, health and environmental standards, and the need for appropriate hydrophobing additives will continue to increase. As availability of paraffin waxes decreases, the security of supply of synthetic waxes will become even more important in the future.

Benefits of using HydroWax dispersions in wood based panels and manufacturing:

- significant cost reduction thanks to the optimized interaction of wax dispersion, press line and glue systems
- improved efficiency and a homogeneous, fine distribution in the panel impart crucial advantages for high-quality subsequent treatments such as direct lacquering, coating and milling
- micro-fine dispersions offer increased compatibility with dosing units to guarantee flexible processing, e.g. incorporation directly into the blow line
- Hywax's entire production process ensures constant product quality from raw material manufacturing to final product transportation
- synthetic waxes allow for exceptionally low levels of edge swelling
- micro-fine dispersions reduce depositing in tanks and pipes, and ensure a stable production processes.

### HydroWax system dispersion

### HydroWax system dispersion


A dispersion's hydrophobing properties are determined by the interaction of water content, wax blend, wax particle size, type of emulsifier and additives, and the emulsion process. Dispersions that are perfectly matched to each individual application provide the best possible swell and process performance. HydroWax offers dispersions for different applications and wood based panels, that range from economic and highly efficient dispersions, to highperformance dispersions that provide maximum hydrophobing performances for special high-end HDF products with sophisticated production lines. Specialty emulsions can also be designed to address specific requirements such as long-term stability or compatibility with high process temperatures. We even offer dispersions for starting up production lines, and for adjusting press performance as agreed

Additives Special properties E.g. viscosity Water Distribution Carrier material Handling Particle size Distribution efficiency & specific wax surface **Key factors** Hydrophobing effect for performance Water absorption **Emulsifier** system Compatibility with pro-Wax blend Hydrophobing effect other chemicals Swelling Water absorption Lubricant properties


with the equipment manufacturer. Our product range includes 100% synthetic dispersions.

### Influence of the particle size on the distribution of wax

The microscopic cross section shows wax particles (blue) covering fibers of an MDF panel (beige). The smaller the wax particles the better the wax distributes within the panel.



Large wax particles; liquid hydrophobing wax, particle size  $\sim$  100  $\mu m.$ 



Conventional dispersion with wax particles


# Micro-fine wax particles – a breakthrough in hydrophobing


HydroWax dispersions with micro-sized wax particles smaller than 400 nm significantly increase overall efficiency. This is due to a combination of the higher number of wax particles and a  $\sim 3.5$  factor increase in wax surface area when compared to conventional emulsions with particle sizes of 1 to 5  $\mu$ m. After extensive research and the development of a multistage manufacturing process, Hywax has succeeded in producing micro-fine dispersions that deliver substantial benefits to the wood-based panel industry:


- Measurably improved hydrophobing and a homogeneous distribution within the wood based panels
- More efficient use of wax and prevention of wax agglomeration (wax stains)


The new HydroWax dispersions with micro protection do not only enhance the wax's performance, but also optimally distribute within the furnish and more efficiently cover from the smallest wood fibres (HDF) up to much larger strands (OSB).

# Multiplication of the wax surface through micro-fine particles











# Micro-fine HydroWax dispersions have the ideal particle size

Wax particles smaller than 400 nm can effectively cover even fine wood fibers. The wax particles distribute more evenly within the wood-based panel and perfectly combine with the glue system. Micro-fine wax particles significantly enlarge the total surface area, resulting in significantly higher efficiency and hydrophobing performance compared to conventional dispersions with wax particles larger than 1,000 nm.



## Synthetic waxes – superior effectiveness

Different paraffin waxes exhibit varying hydrophobing properties when used in wood based panels. Synthetic waxes have proven to be particularly effective. These waxes, produced primarily from natural gas, possess excellent hydrophobing characteristics. Their special composition results in considerably less edge swelling. The superior hydrophobing properties become particularly apparent when the wax is used in small quantities. This means dispersions with a high content of synthetic wax and a relatively low solid content are capable of achieving highly efficient hydrophobing. The synthesis manufacturing process results in synthetic waxes of consistently high quality. Synthetic waxes are fully compatible with paraffin waxes.



Source: Roffael, E. and Schneider, T., 2004, Institute of Wood Technology and Wood Biology



# Contact us:

info@hywax.com +49 40 781150

## Hywax GmbH

Worthdamm 13-27 20457 Hamburg Germany

Hywax is a registered trademark of the AWAX Group. Product trademarks displayed in this document are the property of the AWAX Group, except where it is clear from the context that not. Users of this document are not permitted to use these trademarks without the prior written consent of their proprietor. All rights not expressly granted are reserved. Reference to trademarks used by other companies is neither a recommendation, nor should it give the impression that products of other companies cannot be used.

Disclaimer: The information contained in this document is based on Hywax's knowledge and experience at the time of its creation. We reserve the right to make any changes to this document or the products described therein, as a result of technological progress or developments. This information implies no liability or other legal responsibility on our part, including with regard to existing third-party patent rights. In particular, no guarantee or warranty of properties in the legal sense is implied. The customer is not exempted from the obligation to conduct careful inspection and testing of incoming products.